

EPSON®
EXCEED YOUR VISION



Epson
Stylus Pro **9880**

Set new standards in A0+/B0+ colour and black & white printing

Add quality and productivity to in-house production printing up to 44" wide. Enhance performance in proofing, photography and even fine art with Epson UltraChrome™ K3 ink and Vivid Magenta technology.

Produce superb, contract quality colour and black & white with a single printer. See the difference with Epson UltraChrome K3 ink with Vivid Magenta, an 8-colour ink set with three black inks and improved image-processing technology.

Combine outstanding, repeatable, long lasting results with improved productivity. The printer features new printer drivers, a wide media choice and has both the speed to improve throughput and the reliability for overnight printing.

Ideal for proofing, photography and fine art – get contract quality results for demanding applications

Outstanding colour and black & white printing – achieve superb image quality, high colour stability and maximum tonal gradation

Advanced 8-colour ink set – Epson UltraChrome K3 8-colour ink set with Vivid Magenta and three black inks

Enhanced image processing technology – extended colour representation of reds and blues

Photo realistic quality that lasts – impressive lightfastness for consistent, repeatable quality

Versatile media handling – choose from an extensive range of matte, gloss and fine art finishes

Improved productivity – fast print speeds and high capacity ink cartridges for overnight printing

Simple operation – customise, share and memorise settings with new printer drivers

Key benefits:

- The highest quality A0+ (44") 8-colour production printer
- Epson UltraChrome K3 ink with Vivid Magenta for superb colour
- Neutral black & white and perfectly balanced greyscale
- Improved productivity due to high speed and a wide media choice

Epson Stylus Pro 9880																															
Size	44" (A0+ / B0+)																														
Print technology	Epson Micro Piezo™ drop-on-demand inkjet technology Epson Variable-sized Droplet Technology and 3.5 pl Epson Ultra Micro Dot™ Print head configuration: 180 nozzles x 8 colours																														
Ink system	9 colour pigmented ink (C, VM, Y, LC, VLM, LK, LLK, Photo K, Matte K) with CSiC with 8 slots (one slot for interchangeable Matte K and Photo K) Ink conversion cartridges required for ink change between Matte K and Photo K are delivered with the unit																														
Resolution	2880 x 1440 dpi Bi-Directional, Epson Variable-sized Droplet Technology																														
Speed	Up to 22.1 m ² / Hr (B0+ / Plain paper / Draft mode)																														
Driver	Microsoft® Windows 2000, XP, XP 64-bit, Vista, MAC OS®X 10.x.x																														
Interfaces	Standard: USB 2.0 (compatible with 1.1), Ethernet 10 / 100Mb																														
Roll dimensions	Core diameter 2" or 3". Max. outside diameter Φ150 mm																														
Paper handling																															
Roll media	Single roll (1 roll < 150 mm / outside diameter) Media width 203.2 mm – 1118 mm (8" – 44") Minimum media length 279 mm Media thickness 0.08 mm – 0.50 mm																														
Cut sheet	Manual insertion feeder for media up to 1.5 mm Media width size A4 / LTR – A0+ / 44" (210 mm – 1118 mm) Media thickness 0.08 mm – 1.50 mm																														
Print margins																															
Roll media	3 modes available; mode 1: 3 mm on all edges (top, sides, bottom); mode 2: 15 mm (top and bottom), 3 mm (sides); mode 3: 15 mm (top, sides, bottom)																														
Sheet media	2 modes available; mode 1: 3 mm (top, sides, bottom); mode 2: 3 mm (top and sides) 14 mm (bottom)																														
Edge-to-edge / Borderless																															
Roll media / Cut sheet	Both edge-to-edge and full bleed for the following media widths: 10", 13", 14", 16", 17" 515 mm, 594 mm, 609.6 mm, 728 mm, 914.4 mm, 1117.6 mm Top and bottom edges can be automatically cut to any length																														
Ink cartridges	110 and 220 ml ink capacity, single size packaging Pressurised, Intellidge cartridge system for ink level control even on re-inserted cartridges																														
	<table border="0"> <tr> <td></td> <td>110 ml</td> <td>220 ml</td> </tr> <tr> <td>Matte black</td> <td>C13T611800</td> <td>C13T612800</td> </tr> <tr> <td>Photo black</td> <td>C13T602100</td> <td>C13T603100</td> </tr> <tr> <td>Light black</td> <td>C13T602700</td> <td>C13T603700</td> </tr> <tr> <td>Light light black</td> <td>C13T602900</td> <td>C13T603900</td> </tr> <tr> <td>Cyan</td> <td>C13T602200</td> <td>C13T603200</td> </tr> <tr> <td>Vivid magenta</td> <td>C13T602300</td> <td>C13T603300</td> </tr> <tr> <td>Yellow</td> <td>C13T602400</td> <td>C13T603400</td> </tr> <tr> <td>Vivid light magenta</td> <td>C13T602600</td> <td>C13T603600</td> </tr> <tr> <td>Light cyan</td> <td>C13T602500</td> <td>C13T603500</td> </tr> </table>		110 ml	220 ml	Matte black	C13T611800	C13T612800	Photo black	C13T602100	C13T603100	Light black	C13T602700	C13T603700	Light light black	C13T602900	C13T603900	Cyan	C13T602200	C13T603200	Vivid magenta	C13T602300	C13T603300	Yellow	C13T602400	C13T603400	Vivid light magenta	C13T602600	C13T603600	Light cyan	C13T602500	C13T603500
	110 ml	220 ml																													
Matte black	C13T611800	C13T612800																													
Photo black	C13T602100	C13T603100																													
Light black	C13T602700	C13T603700																													
Light light black	C13T602900	C13T603900																													
Cyan	C13T602200	C13T603200																													
Vivid magenta	C13T602300	C13T603300																													
Yellow	C13T602400	C13T603400																													
Vivid light magenta	C13T602600	C13T603600																													
Light cyan	C13T602500	C13T603500																													
Lightfastness	Up to 75 years for colour prints In excess of 100 years for B&W prints																														
General																															
Dimensions (WxDxH)	1702 x 678 x 1196 mm																														
Weight	Approx. 90 kg without ink and media																														
Noise level	Approx. 50 dB																														
Power consumption	Printing: 50 W or less Standby: 6 W or less Power off: 1 W or less																														
Warranty	1 year on-site repair Optional extension to 3 years																														
Options	2 / 3" dual roll feed spindle (high tension) C12C811152 Maintenance tank (x2) C12C890191																														



Telephone: 08702 416900 (UK)
1 800 409132 (Republic of Ireland)
E-mail: info@epson.co.uk

www.epson.co.uk
www.epson.ie
Fax: +44 (0) 8702 413093